



Features :

- 110 IDC connector compatible
- Provides termination for 22~26 AWG wire
- IDC insertion life >250 mating cycles
- Operating temperature : -40°C~+60°C

Electrical :

- Contact resistance : 20M ohm
- DC Current rating : 1.5Amps
- DC resistance : Max. 0.1 ohm
- Insulation Resistance : 500m ohm
- Dielectric withstanding voltage : 1000V

| TOLERANCE |      |
|-----------|------|
| .XXXX     | ---  |
| .XXX      | 0.10 |
| .XX       | 0.25 |
| .X        | 0.38 |

MATERIAL

|             |   |
|-------------|---|
| PLASTIC     | PC UL94V-0  |
| METAL FRAME | SPCC  |
| EXCLOSURE   | ID LABEL HOLDER x 2PCS , ID LABEL x 2PCS , CABLE TIE x 4PCS |
| ACCESSORIES | 4pair 110 connector x 20pcs , 5pair 110 connector x 4pcs    |
|             |   |
|             |   |
|             |   |

P/NO. SY-110-100RM-A

|                       |        |                     |
|-----------------------|--------|---------------------|
| ITEM.                 | CO. SY | FILE.SY-110-100RM-A |
| DR. Breaker2009/04/13 | APPD.  | CHKD.               |



Shiunn Yang Ent.Co.Ltd.  
 TEL: 29089890 <REP>  
 FAX: 29068849,29088679

|           |         |
|-----------|---------|
| SCALE 1/1 |         |
| UNIT mm   | SIZE A4 |
| SHEET     | REV.    |