



Date	2009/04/13
Revision	A

Features :

- 110 IDC connector compatible
- Provides termination for 22~26 AWG wire
- IDC insertion life >250 mating cycles
- Operating temperature : -40°C~+60°C

Electrical :

- Contact resistance : 20M ohm
- DC Current rating : 1.5Amps
- DC resistance : Max. 0.1 ohm
- Insulation Resistance : 500m ohm
- Dielectric withstanding voltage : 1000V

TOLERANCE	
.XXXX	---
.XXX	0.10
.XX	0.25
.X	0.38

MATERIAL

PLASTIC	PC UL94V-0
METAL FRAME	SPCC
EXCLOSURE	ID LABEL HOLDER x 4PCS , ID LABEL x 4PCS , CABLE TIE x 8PCS
ACCESSORIES	4pair 110 connector x 40pcs , 5pair 110 connector x 8pcs

P/NO. SY-110-200RM-A

ITEM.	CO. SY	FILE.SY-110-200RM-A
DR. Breaker2009/04/13	APPD.	CHKD.



Shiunn Yang Ent.Co.Ltd.
 TEL: 29089890 <REP>
 FAX: 29068849,29088679

SCALE 1/1	
UNIT mm	SIZE A4
SHEET	REV.