

1	2	3	4	5	6	7
ROHS Compliant						DATE 2022/12/22
						Revision C
A						A
B						B
C						C
D						D
E						E

Supporting Bar

1.02±0.02

6.35±0.1

9.35±0.1

1.02±0.02

2.5±0.1

3.9±0.1

3.9±0.1

1.02±0.02

2 prongs For Solid Wires

5.89±0.10

2.77±0.10

5.8±0.10

8.3±0.15

13.50±0.10

22.75±0.15

1.02±0.05

6.10±0.07

3.25±0.10

10.15±0.10

11.68±0.10

TOLERANCE	
.XXX	0.10
.XX	0.25
.X	0.38

MATERIAL			
HOUSING	☐ PC UL94V-0 ☒ PC UL94V-2	TYPE OF PLUG	☒ SHIELD ☐ UNSHIELD
CONTACT	PHOSPHOR BRONZE FINE GOLD	GOLD-PLATING	☐ 0.15U M/6U" MINIMUM ☐ 0.38U M/15U"MINIMUM
	PLATED OVER NICKEL		☐ 0.76U M/30U"MINIMUM ☒ 1.27U M/50U"MINIMUM
APPLICATION	☐ UTP CAT.5E ☐ UTP CAT.6 ☐ STP CAT.5E ☒ STP CAT.6		
	☒ SOLID ☐ STRANDED		
REV.	DESCRIPTION	ENG.	APPROVAL

P/NO. SY-FRJ2-45-3		
ITEM. Modular Plug	CO. SY	S/N. SY-FRJ2-45-3
DR.	APPD. Sweet 2022/12/22	CHKD.
Shiunn Yang Ent.Co.Ltd. TEL: 29089890 <REP> FAX: 29088679		FILE. SY-FRJ2-45-3
		SCALE /
		UNIT mm SIZE A4